

# AMST<sub>E</sub>X Reference Card

(See the T<sub>E</sub>X Reference Card for further commands)

## Formatting

<code>\pagewidth{&lt;dimen&gt;}</code>	set page width
<code>\pageheight{&lt;dimen&gt;}</code>	set page height
<code>\hcorrection{&lt;dimen&gt;}</code>	move page right
<code>\vcorrection{&lt;dimen&gt;}</code>	move page down
<code>\flushpar</code>	start a paragraph with no indentation
<code>\boxed#1</code>	boxed formula
<code>\NoBlackBoxes</code>	omit overfull hbox markers
<code>\comment ... \endcomment</code>	unprinted comments
<code>\pageno#1</code>	set page number
<code>\nopagenumbers</code>	turn off page numbering if not using <code>amsptt</code> style

## Fonts

### Text Fonts

<code>\rm</code>	roman
<code>\it</code>	italic
<code>\bf</code>	boldface
<code>\sl</code>	slant
<code>\smc</code>	small capitals

### Math Mode Fonts

<code>\bold#1</code>	bold letter
<code>\loadbold</code>	load bold math symbols
<code>\boldkey#1</code>	bold keyboard symbol
<code>\boldsymbol#1</code>	bold math symbol (e.g. $\alpha$ )
<code>\Cal#1</code>	caligraphic (script) upper case
<code>\frak#1</code>	German Fraktur
<code>\goth#1</code>	German Fraktur (same as <code>\frak</code> )
<code>\Bbb#1</code>	blackboard bold
<code>\rom#1</code>	Roman

### Loading Fonts & Symbols (if not using `amsptt` style)

<code>\loadmsam</code>	load <code>msam</code> symbol font
<code>\loadmsbm</code>	load <code>msbm</code> symbol font
<code>\UseAMSsymbols</code>	define all symbols from <code>msam</code> , <code>msbm</code> fonts
<code>\newsymbol</code>	define a particular symbol

### Changing Font Sizes

<code>\tenpoint</code>	use 10 point fonts
<code>\eightpoint</code>	use 8 point fonts
<code>\dsize</code>	use display size
<code>\tsize</code>	use text size
<code>\ssize</code>	use subscript size
<code>\sssize</code>	use subsubscript size

## Macro Definitions

<code>\define\cs{...}</code>	define a control sequence
<code>\redefine\cs{...}</code>	redefine a control sequence
<code>\predefine\newcs{\oldcs}</code>	assign new name to a control seq
<code>\operatorname#1</code>	new operator name
<code>\operatornamewithlimits#1</code>	new operator name with limits
<code>\newsymbol</code>	new symbol from <code>msam</code> , <code>msbm</code> fonts

## Footnotes and Insertions

<code>\footnote#1</code>	footnote
<code>\footnote"*#1</code>	footnote with specified marker
<code>\topinsert ... \endinsert</code>	insert at top of page
<code>\midinsert ... \endinsert</code>	insert in middle of page
<code>\topcaption#1 ... \endcaption</code>	caption at top of insert
<code>\botcaption#1 ... \endcaption</code>	caption at bottom of insert
<code>\vspace{&lt;dimen&gt;}</code>	leave vertical space in an insert

## Hyphenation

<code>\showhyphens#1</code>	show allowable hyphens
<code>\-</code>	discretionary hyphen
<code>\hyphenation#1</code>	add words to hyphenation list

## Fractions and Such

<code>\frac#1#2</code>	fraction
<code>\dfrac#1#2</code>	display size fraction
<code>\tfrac#1#2</code>	text size fraction
<code>\fracwithdelims()#1#2</code>	fraction with paren. delimiters
<code>\binom#1#2</code>	binomial coefficient
<code>\dbinom#1#2</code>	display size binomial coefficient
<code>\tbinom#1#2</code>	text size binomial coefficient
<code>\underset#1\to#2</code>	typeset #1 under #2
<code>\overset#1\to#2</code>	typeset #1 over #2
<code>\overbrace#1^#2</code>	overbrace with label above
<code>\underbrace#1_#2</code>	underbrace with label below
<code>\sideset~#1\and~#2\to\bigop</code>	superscripts on side of operator
<code>\cfrac ... \endcfrac</code>	continued fraction
<code>\lcfrac ... \endcfrac</code>	continued fraction flush left
<code>\rcfrac ... \endcfrac</code>	continued fraction flush right

## Arrows & Commutative Diagrams

<code>@&gt;#1&gt;#2&gt;</code>	right arrow with labels
<code>@&lt;#1&lt;#2&lt;</code>	left arrow with labels
<code>\CD ... \endCD</code>	commutative diagram (don't use &'s)
<code>@V#1V#2V</code>	down arrow with labels
<code>@A#1A#2A</code>	up arrow with labels
<code>@=</code>	long horizontal = sign
<code>@ </code>	long vertical equal sign
<code>@.</code>	leave out an arrow
<code>\pretend#1\haswidth#2</code>	make arrows longer

## Accents

Type	Example	In Math	In Text
hat	$\hat{a}$	<code>\hat</code>	<code>\^</code>
expanding hat	$\widehat{abc}$	<code>\widehat</code>	none
check	$\check{a}$	<code>\check</code>	<code>\v</code>
tilde	$\tilde{a}$	<code>\tilde</code>	<code>\~</code>
expanding tilde	$\widetilde{abc}$	<code>\widetilde</code>	none
acute	$\acute{a}$	<code>\acute</code>	<code>\'</code>
grave	$\grave{a}$	<code>\grave</code>	<code>\`</code>
dot	$\dot{a}$	<code>\dot</code>	<code>\D</code>
double dot	$\ddot{a}$	<code>\ddot</code>	<code>\"</code>
breve	$\breve{a}$	<code>\breve</code>	<code>\u</code>
bar	$\bar{a}$	<code>\bar</code>	<code>\B</code>
vector	$\vec{a}$	<code>\vec</code>	none
cedilla	$\ç$	none	<code>\c</code>

## Dimensions

Dimensions are specified as (number)(unit of measure).

point	pt	pica	pc	inch	in	centimeter	cm
m width	em	x height	ex	math unit	mu	millimeter	mm
1 pc = 12 pt		1 in = 72.72 pt		2.54 cm = 1 in		18 mu = 1 em	

## Spacing and Dots

<code>\linebreak</code>	force a line break
<code>\newline</code>	force a new line, old line pushed left
<code>\mathbreak</code>	force line break
<code>\allowmathbreak</code>	allow line break
<code>\-</code>	discretionary hyphen
<code>\.</code>	abbreviation period
<code>\,</code> or <code>\thinspace</code>	thin space
<code>\medspace</code>	medium space
<code>\;</code> or <code>\thickspace</code>	thick space
<code>\!</code> or <code>\negthinspace</code>	negative thin space
<code>\negmedspace</code>	negative medium space
<code>\negthickspace</code>	negative thick space
<code>\quad</code>	quad space
<code>\qquad</code>	double quad space
<code>%</code>	comment line
<code>\</code>	one blank space
<code>\phantom#1</code>	blank space size of #1
<code>\hphantom#1</code>	blank space width of #1, no height
<code>\vphantom#1</code>	blank space height of #1, no width
<code>\smash#1</code>	ignore height and depth
<code>\topsmash#1</code>	ignore height
<code>\botsmash#1</code>	ignore depth
<code>\mathstrut</code>	strut to help vertical spacing
<code>\smallpagebreak</code>	small space between paragraphs
<code>\medpagebreak</code>	medium space between paragraphs
<code>\bigpagebreak</code>	big space between paragraphs
<code>\pagebreak</code>	force a page break
<code>\nopagebreak</code>	forbid a page break
<code>\newpage</code>	force a page break fill page with blank space
<code>\hdots</code>	horizontal dots
<code>\vdots</code>	vertical dots
<code>\ddots</code>	diagonal dots
<code>\dots</code>	dots in text or formulas
<code>\ldots</code>	low dots in text or formulas
<code>\cdots</code>	center dots in text or formulas

## Miscellaneous Operations

<code>\bmod#1</code>	mod as binary operation
<code>\pmod#1</code>	mod with parentheses
<code>\mod#1</code>	same as <code>pmod</code> , but no parens
<code>\pod#1</code>	parentheses, but no "mod"
<code>\sqrt#1</code>	square root
<code>\root#1\of#2</code>	root
<code>\uproot{&lt;number&gt;}</code>	move root up/down
<code>\leftroot{&lt;number&gt;}</code>	move root left/right
<code>\iiint</code>	two integral signs
<code>\iiint</code>	three integral signs
<code>\idotsint</code>	integral signs with dots

## AMS Preprint Style

`\input amstex`  
`\documentstyle{amsppt}`  
 (Preamble Commands)  
`\topmatter`  
 (Top Matter Commands)  
`\endtopmatter`  
`\document`  
 (Body of Document)  
`\enddocument`  
**Preamble Commands**  
`\TagsOnLeft` (default) or `\TagsOnRight`  
`\TagsAsText` (default) or `\TagsAsMath`  
`\NoPageNumbers`  
`\NoRunningHeads`  
`\Monograph`  
`\define`  
**Top Matter Commands**  
`\title ... \endtitle`  
`\author ... \endauthor`  
`\affil ... \endaffil`  
`\address ... \endaddress`  
`\curraddr ... \endcurraddr`  
`\email ... \endemail`  
`\date ... \enddate`  
`\dedicatory ... \enddedicatory`  
`\thanks ... \endthanks`  
`\translator ... \endtranslator`  
`\keywords ... \endkeywords`  
`\subjclass ... \endsubjclass`  
`\abstract ... \endabstract`  
`\toc ... \endtoc` (Table of Contents)  
`\leftheadtext#1` (set left headline text)  
`\rightheadtext#1` (set right headline text)  
**Body of Paper Commands**  
`\specialhead ... \endspecialhead`  
`\head ... \endhead`  
`\subhead ... \endsubhead`  
`\subsubhead ... \endsubsubhead`  
`\proclaim#1 ... \endproclaim`  
`\rom#1` (Roman font in proclaim)  
`\demo#1 ... \enddemo` (proof)  
`\qed` (end of proof marker)  
`\roster ... \endroster` (roster of listed items)  
`\item` (start a new item in a roster)  
`\item[(number)]` (specify roster item number)  
`\item"*` (item with specified marker)  
`\therosteritem#1` (refer to specified roster item)  
`\widestnumber\item#1` (set width for roster labels)  
`\nofrills` (turn off automatic font, spacing, punctuation)  
`\usualspace` (usual space following punctuation)  
`\definition#1 ... \enddefinition`  
`\example#1 ... \endexample`  
`\remark#1 ... \endremark`  
`\block ... \endblock` (indented text)  
`\cite` (cite a reference)

## AMS Preprint Style — References

`\Refs ... \endRefs` list of references  
`\refstyle#1` specify style A, B, or C  
 A = initials, B = name, C = number  
`\ref ... \endref` individual reference  
`\no or \key` number or key for reference  
`\widestnumber\no#1` or `\widestnumber\key#1`  
`\by` author  
`\bysame` same as previous author  
`\paper` name of paper  
`\vol` volume  
`\yr` year of publication  
`\jour` journal  
`\page or \pages` page(s)  
`\toappear` to appear  
`\inbook` article in a book  
`\moreref` additional reference information  
`\paperinfo` extra information after paper title  
`\procinfo` information about proceedings  
`\issue` issue number  
`\lang` language  
`\transl` information about translated version  
`\book` book  
`\ed or \eds` editor(s)  
`\publ` publisher  
`\publaddr` publisher address  
`\bookinfo` extra information after book title  
`\finalinfo` extra information for end  
`\miscnote` same as `\finalinfo`, in parens.

## Overlines and Underlines

`\underline#1` underline  
`\overline#1` overline  
`\overarrow#1` over right arrow  
`\underarrow#1` under right arrow  
`\overleftarrow#1` over left arrow  
`\underleftarrow#1` under left arrow  
`\overleftrightarrow#1` over left-right arrow

## Delimiters

`[ \lbrack` or `\l[` { `\lbrace` or `\{` `<` `\langle`  
`]` `\rbrack` or `\]` } `\rbrace` or `\}` `>` `\rangle`  
`|` `\vert` or `\|` `⌊` `\lfloor` `⌈` `\lceil`  
`||` `\Vert` or `\|` `⌋` `\rfloor` `⌉` `\rceil`  
`↑` `\uparrow` `↕` `\Uparrow` `⇕` `\updownarrow`  
`↓` `\downarrow` `⇓` `\Downarrow` `⇩` `\updownarrow`  
`⌈` `\lceil` `((` `\l(` `⟨` `\langle` `\!` `\!` `\rangle`  
`⌋` `\rceil` `)` `\!` `\!` `\rangle` `\!` `\!` `\rangle`

`\left#1 \right#1` expanding delimiters  
`\left.` `\right.` empty delimiters  
`\bigl#1 \bigr#1` big delimiters  
`\Bigl#1 \Bigr#1` bigger delimiters  
`\biggl#1 \biggr#1` even bigger delimiters

## Non-Italic Function Names

`\arccos` `\cos` `\csc` `\exp` `\ker` `\limsup` `\min` `\sinh`  
`\arcsin` `\cosh` `\deg` `\gcd` `\lg` `\ln` `\Pr` `\sup`  
`\arctan` `\cot` `\det` `\hom` `\lim` `\log` `\sec` `\tan`  
`\arg` `\coth` `\dim` `\inf` `\liminf` `\max` `\sin` `\tanh`

## Alignments and Displayed Equations

`\` separate lines  
`&` separate items in a line  
`\align ... \endalign` align equations, full width of page  
`\alignat#1 ... \endalignat` align #1 pairs  
`\xalignat#1 ... \endxalignat` equally spaced  
`\xxalignat#1 ... \endxxalignat` equally spaced, flush  
`\aligned ... \endaligned` align equations, width as needed  
`\alignedat#1 ... \endalignedat` align #1 pairs  
`\topaligned ... \endtopaligned` align along top  
`\botaligned ... \endbotaligned` align along bottom  
`\gather ... \endgather` centered equations, full width of page  
`\gathered ... \endgathered` centered equations, width as needed  
`\multiline ... \endmultiline` first line left, middle lines centered, last line right  
`\shoveleft#1` shove lines left  
`\shoveright#1` shove lines right  
`\multlinegap{<dimen>}` change margins  
`\cases ... \endcases` case construction  
`\split ... \endsplit` align split equations with variable tag placement  
`\Sb ... \endSb` multi-line subscript  
`\Sp ... \endSp` multi-line superscript  
`\text#1` text within formula  
`\intertext#1` text between lines  
`\foldedtext#1` lines of text in formula  
`\topfoldedtext#1` top-aligned folded text  
`\botfoldedtext#1` bottom-aligned folded text  
`\foldedwidth{<dimen>}` set width of folded text  
`\allowdisplaybreak` allow page break after line  
`\allowdisplaybreaks` allow page breaks after any line  
`\displaybreak` force page break after line  
`\vspace{<dimen>}` extra space between two lines  
`\spreadlines{<dimen>}` extra space between every line  
`\spreadmatrixlines{<dimen>}` same for a matrix  
`\jot` unit of vertical space  
`\tag#1` tag for a formula  
`\thetag#1` refer to tag in current style  
`\tag"*` tag exactly as specified  
**Matrices**  
`\matrix ... \endmatrix` matrix alignment  
`\pmatrix ... \endpmatrix` matrix with parentheses  
`\bmatrix ... \endbmatrix` matrix with brackets  
`\vmatrix ... \endvmatrix` matrix with vertical lines  
`\Vmatrix ... \endVmatrix` matrix with double vertical lines  
`\smallmatrix ... \endsmallmatrix` small matrix  
`\format` specify a format for a matrix  
`\c \l \r` format entry center, left, right

Copyright © 1998 J.H. Silverman, November 1998 v1.3  
 Math. Dept., Brown Univ., Providence, RI 02912 USA  
 T<sub>E</sub>X and AMST<sub>E</sub>X are trademarks of the American Mathematical Society  
 Permission is granted to make and distribute copies of this card provided the copyright notice and this permission notice are preserved on all copies.